

ES

Artikel nr: 7636

Thickened environmentally friendly paint remover , take if you wish, layer after layer .

ES is a user-friendly paint remover for use indoors and outdoors, for example wood, stone , metal. ES requires dry surface during application and duration of action. ES contains organic solvents which both solves and brings the vast majority of colors, including acrylic, alkyd , linseed oil, phenol resins , polyvinyl acetate , styrene, urethane, amines, cellulose paints, epoxy, white lead .

ES is readily biodegradable. Etches not " modern " glass (except plexiglass) . ES, however, a temperature sensitive product . Best temperature +20 +30 ° C. The lowest temp. +10 ° C. Ev . add heat , but maximum 60 ° C. Protect sensitive nature and objects that can not be treated. Tarpaulin light ?

TREATMENT SURFACE:

Do not process the surface before with high-pressure water, without applying concentrated ES on pristine dry surface with airless paint sprayer min. 200 bar for larger areas , alt . brush that is used as a putty knife. Apply superfluous and even thickness , surface color without pressing the shutter colorless , always from the bottom up . On the smaller details can brush / spatula or cloth used. Major details are added in the bath. Let stand until the paint is dissolved. Reaction time from 15 minutes to 48 hours, giving a controlled color solution , layer after layer of different colors. Caution should be taken if the surface underneath is linoleum, vinyl , pvc or other plastic surface

ES method of standing surface recommendation :

1) applying a bottom-up 'normal' stock as attachment layer , 0.1-0.2 l / sqm / stock of ES .
2) Wait 10-20 minutes, apply again superfluous and even thickness outside of the first coat , 0.4-0.5 l / sq / / store.

As the weather (except the roof) , the odor and for better wetting, attachment UV safe thin plastic wrap from the bottom up . We recommend 3M Scotch Blue Painters Tape , 2090FRS -M or L , or equivalent outside. Avoid air bubbles , and let the foil attached statically on the paint remover , bottom to top . Manage the foil carefully. Use a wallpaper brush gently outside the foil from the bottom up . Dense at the top of the plastic film horizontally against rain by a suitable waterproof adhesive tape .

3) If necessary, after one day and the plastic removed, further laying on the outside of the first few layers. The plastic on . ES wipe out the excessive hot surface , such as on the tin roof over weekend. However, you can dissolve the ES with additional application on top.

Our recommendation outdoors : Apply early morning. Then you have the most control of the temperature / time and weather . And ev . additional protection for the dew and rain, heat , light tarp ?

Reaction time :

Add heat to achieve the best results. Monitor the duration the first time and note the circumstances to succeed best.

After duration of action:

The scraper must be adapted to the substrate. Use appropriate tools, from plastic knife , nail brush , click scraper, to ergonomic Bahco electricity. Like! . scrape with wavy metal blade or squeegee . Rinse with warm water up to 90 ° C and eg fungi. Allow to dry thoroughly . No rotating water jets against wood fibers ! See also more about the ES method, www.takcare.se

Materials: Calculate with 0.5-0.7 l / square meter warehouse, depending on temperature and coating thickness.

Technical data:

- Viscous yellowish liquid
- Available in 1, 5, 10 and 25 liter plastic containers
- Specific weight 0.99 kg / liter. • Low odor , however, varies a little with different lot in the ingredients

• Flash point 80 ° C

• Contains: N-ethyl- 2-pyrrolidone (NEP)

Storage

Store in original closed container at room temperature.

durability

Approximately 24 month. unopened .

Protective

Always wear close-fitting eye protection and appropriate gloves , such as PVC that is discarded after the day's end.

Provide adequate ventilation when paint removal in confined space.

Risk of serious damage to eyes.

The product is not classified as dangerous goods .

Keep from freezing , however dark and cool .

Environmental Considerations : If possible, take care of the old paint on environmentally sound. manner when it is encased in the thickened pulp with colorless successor



labeling

irritant

Protect sensitive nature and gullies . Tip: Denios Environmental Protection & Safety, www.denios.se .

Incidentally : Light Covers .

Before You take care of the dissolved color should / should you check with local authorities which rules apply .

See safety data sheet on www.takcare.se

Let time do the job !

. This product information is intended as a guide of the product handling,

Why takcare not give any guarantee for the result achieved. Applicator of product shall carry out testing and be responsible for the result.

takcare

S-746 33 Bålsta, Sweden | Tfn: 0046 859031820 | Mobil: 0046 707880320 | info@takcare.se | www.takcare.se